Veeto Hobbies India

Plot no. 413, HSIIDC Industrial Area (Saha) Ambala (Haryana)

Website: www.veeto.co.in, E-mail: veetohobbies@hotmail.com Ph: +91-7027002328/29/75, 0171-2822788

Technical Data Sheet

Middle Chrome V-11

Middle Chrome V-11 is a monoclinic lead chromate and is recommended for Paints, Printing Inks, Road Marking Paints and Plastic Master Batch Industries. A special characteristic of this product is the high purity in shade and clean Full Tone. This Pigment is stabilized and offers good resistance to light and weather. This pigment also has good dispersion characteristics.

Color Index No.			77603	
Color Index Pigme	nt No.		Y-34	
Oil Absorption			15-25	
Specific Gravity			5.1-6.0	
Bulk Density g/cc			0.89	
		BLEEDING IN		
Water			5	
5%CausticSoda			3	
5%HydrochloricAcid			3	
Linseed Oil			5	
Ethanol			5	
Ethyl Acetate			5	
Xylene			5	
n-Butanol			5	
Methyl Ethyl Ketone			5	
Mineral Turpentine			5	
Cellosolve			5	
Dioctyl Phthalate			5	
•	RES	ISTANCE TO HEAT		
120°C/ 30min.			SB	
150°C/ 20min.			SB	
180°C/ 10min.			SB	
220°C/ 10min.			SB	
240*C-250*C/10MIN.			SB	
	RES	ISTANCE TO LIGHT		
Full Tone			7	
Tint Tone(1:10)			6	
	ſ	RESISTANCE TO		
Acid			G	
Alkali			F	
		APPLICATIONS		
Paints			*	
Printing Inks			*	
Rubber				
Leather Pastes			*	
Linoleum			*	
PVC Leather Cloth			*	
Paper Coating		*		
Chalk / Crayons				
Plastics			*	
BLEEDING	HEATSTABILITY	LIGHTFASTNESS	APPLICATIONS	E-EXCEL

COLOUR	BLEEDING	HEATSTABILITY	LIGHTFASTNESS	APPLICATIONS	E-EXCELLENT
Y-YELLOW	SCALE(1-5)	SB:STABLE	SCALE(1-8)	*RECOMMENDED/MA Y BE USED	VG-VERYGOOD
R-RED	5:NOBLEED	USB:UNSTABLE	1-POOR		G-GOOD
W –WHITE	1:CONSIDERABLEBLLED		8-EXCELLENT		F– FAIR
					P- POOR

Disclaimer: The above information is true to the best of our knowledge. We shall, however, not be responsible for any loss, injury or damage that may result from the use of this information.